

## Something that is good can also be made even better!

Connect and get going: our CONNECTUS power strip has stood for this simplicity for years. With over one million units sold, it is clear that you cannot get such level of professional quality at such a fair price anywhere else. Ideal for the fully and semi-professional worlds!

The reliable CONNECTUS power strip is back with lasting quality, bringing a whole range of new features and impressive practical details. Additional mounting holes open up further attachment options. This means that the power strip can be mounted permanently with screws or nails and temporarily with cable ties almost anywhere. With features such as up to 12 slots, the practical power switch and the mains and frequency filter, CONNECTUS is keeping up with the times. The new optional 22 watt USB charger makes it particularly easy to power smartphones, tablets and other mobile devices without requiring an additional power supply unit.

## **Benefits**

- Fast charging that is easy on the battery thanks to the USB-A/C charger
- A range of versions
- Optimised cable rewind
- A wide range of mounting options
- Professional quality at the best price



Find out more: www.bachmann.com/connectus









# ORM FACILITATE CONNECT

#### THE NEW CONNECTUS

Your ideal companion for a huge range of



While professional craftspeople appreciate its reliable quality, hobbyists benefit from its practical new USB function, and small and medium-sized companies are impressed by its value for money.

Even schools and public authorities are taking advantage of the new CONNECTUS: the high quality standards and the new orange coloured end caps, available as an option, ensure maximum safety in public spaces.

Enjoy the benefits of the new CONNECTUS: this high-quality power strip features state-of-the-art functions and comes at a very reasonable price. Simple and practical: CONNECTUS continues to be THE power strip for everyone who wants to focus on the essentials.

#### **CONNECTUS**

- Supply cable: 2.0 m H05VV-F3 G 1.5 mm², black
- with right-angled plug with earthing contact
- Plastic profile: grey
- Designer end caps including elongated hole for wall mounting and the option of mounting with cable ties, black

#	$\odot$	$\odot$	<u>•</u>	4	*	(f) <sup>†</sup>	**+	$ \Longleftrightarrow $	<b>1</b>	F-1-3-3-3-3-3-3-3-3-3-3-3-3-3-3-3-3-3-3-
BM005901	12		•					709 x 74 x 43 mm		
BM005902	9		•					582 x 74 x 43 mm		BM005902
BM005905	6		•					454 x 74 x 43 mm		
BM005906	4		•					360 x 74 x 43 mm		2222
BM005932		6	•					454 x 74 x 43 mm		F 200000
BM005933		4	•					360 x 74 x 43 mm		
With externa	button	l.5 m cable	to plug   1	.5 m cable	to switch					BM005932
BM005907	6							700 x 74 x 43 mm		
With overvol	tage prote	ction								1 3 3 3 3 3 3 3
BM005904	6		•	•				496 x 74 x 43 mm		1 13 3 3 3 3
With PLUS o	vervoltage	protection	1							BM005904
BM005925	6		•			•		490 x 74 x 43 mm		
With PLUS o	vervoltage	protection	and PLUS	6 interfere	nce suppre	ession filte	r			
BM005924	6		•			•	•	582 x 74 x 43 mm		F F F G 3333
With overvol	tage prote	ction and i	nterferenc	e suppres	sion filter					
BM005903	6		•	•	•			582 x 74 x 43 mm		BM005931
BM005931		6	•	•	•			582 x 74 x 43 mm		
With USB A/	C 22 W ch	arger								E
BM005920	6		•					516 x 74 x 43 mm	A&C 22 W	
BM005939		6	•					516 x 74 x 43 mm	A&C 22 W	BM005920

### **CONNECTUS**

- Supply cable: 2.0 m H05VV-F3 G 1.5 mm<sup>2</sup>, black
- with right-angled plug with earthing contact
- Plastic profile, black
- Designer end caps including elongated hole for wall mounting and the option of mounting with cable ties, black

#	$\odot$	$\odot$	0	4		<b>3</b> <sup>+</sup>	** +	$ \Longleftrightarrow $	<b>4</b>
BM005908	12		•					709 x 74 x 43 mm	
BM005909	9		•					590 x 74 x 43 mm	
BM005912	6		•					454 x 74 x 43 mm	
BM005913	4		•					360 x 74 x 43 mm	
BM005935		6	•					454 x 74 x 43 mm	
BM005936		4	•					360 x 74 x 43 mm	
With external button   1.5 m cable to plug   1.5 m cable to switch									
BM005914	6							700 x 74 x 43 mm	
With overvol	tage prote	ction							
BM005911	6		•	•				490 x 74 x 43 mm	
With PLUS o	With PLUS overvoltage protection								
BM005927	6		•			•		490 x 74 x 43 mm	



#### **CONNECTUS**

- Supply cable: 2.0 m H05VV-F3 G 1.5 mm², black
- with right-angled plug with earthing contact
- Plastic profile, black
- Designer end caps including elongated hole for wall mounting and the option of mounting with cable ties, black

#	$\odot$	$\odot$	0	4	*	<b>3</b> <sup>+</sup>	mt+	$ \Longleftrightarrow $	<b>*</b>	8 FRICE 19393
With PLUS o	vervoltage	protection	n and PLUS	S interfere	nce suppre	ssion filter				
BM005926	6		•			•	•	582 x 74 x 43 mm		BM005926
With overvol	tage prote	ction and i	nterferenc	e suppres	sion filter					a
BM005910	6		•	•	•			582 x 74 x 43 mm		
BM005934		6	•	•	•			582 x 74 x 43 mm		BM005910
With USB A/	C 22 W ch	arger								a 1110000000
BM005922	6		•					590 x 74 x 43 mm	A&C 22 W	I E O O O
BM005941		6	•					590 x 74 x 43 mm	A&C 22 W	BM005941

#### **CONNECTUS**

- Supply cable: 2.0 m H07BQ-F3 G 1.5 mm<sup>2</sup>, orange
- with right-angled plug with earthing contact
- Plastic profile, black
- Designer end caps including elongated hole for wall mounting and the option of mounting with cable ties, orange

#	$\odot$	$\odot$	0	9	**	$ \Longleftrightarrow $	
BM005918	9		•			590 x 74 x 43 mm	
BM005917	6		•			454 x 74 x 43 mm	
BM005919	4		•			360 x 74 x 43 mm	
BM005937		6	•			454 x 74 x 43 mm	
BM005938		4	•			360 x 74 x 43 mm	
With overvoltage protection							
BM005916	6		•	•		490 x 74 x 43 mm	
With overvoltage protection and interference suppression filter							
BM005915	6		•	•	•	582 x 74 x 43 mm	



#### **CONNECTUS**

- Supply cable: 2.0 m H05VV-F3 G 1.5 mm², black
- with IEC C14 non-heating device plug
- Socket colour: red
- Plastic profile: grey
- Designer end caps including elongated hole for wall mounting and the option of mounting with cable ties, black

#	$\odot$	$ \Longleftrightarrow $
10 A micro fu	use	
BM005928	3	327 x 74 x 43 mm